

The new Excalibur Sport with Pedal Force Measurement

Smarter, Better, Stronger!



Highlights

Extreme workload range of 10 - 3000 watt

This extraordinary peak workload is extremely suitable for sports medicine and testing the strongest athletes on their anaerobic power or isokinetic capacity. Combined with the low start workload of 10 Watt this Excalibur will fit everybody.

Left and right independent measurements

The PFM is not only the summation of left and right, but real left and right independent measurements. Differences between the left and right pedal movement, before and after surgery or at different workload can be detected. A real diagnostic tool!

Measurement every 2 degrees

The accuracy of the PFM during the total revolution is obtained by the placement of highly specific strain gauges in the crank axis making it possible to measure the pedal force every 2 degrees during each revolution during the exercise test.

Special Analysis and Polar Graphs

Analysis and Polar graphs are specifically designed for pedal force measurement

LEM PFM included

The LEM software with PFM module is standard included



The new Excalibur Sport with Pedal Force Measurement



Smarter, Better, Stronger!

With its unbeatable accuracy and reliability, the Excalibur Sport has proven itself as The Gold Standard in Ergometry ever since 1985. However, the world keeps spinning and developments never stop. That is why we now proudly present the **new Lode Excalibur Sport**: Smarter, Better and Stronger! Still true to its heritage but combined with innovative new features to meet the latest and future requirements of modern sports medicine and research to allow athletes to become stronger and better with smarter use of human performance technology.

Versatile ergometer

The new Lode Excalibur Sport ergometer is an essential part of a sports medicine or research lab, since it can be used to test all types of athletes. The ergometer allows for various tests, like a Wingate sprint test, Isokinetic tests, High Intensity Tests (HIT) and time trials. Moreover, it can also be used for CPET testing and bike fitting.

Pedal Force Measurement


This Excalibur sport has built-in modified strain gauge technology that measures forces exerted on the pedals during exercise and is supplied with angle detection. Independent measurements of forces in both left and right crank are possible. Wireless transmission of the measured forces to the PC by blue tooth. Note: this setting is supplied with LEM and LEM PFM software (various other modules are available), a computer (we recommend to use this PC only for the LEM software) and an interface cable.

The new Excalibur Sport with Pedal Force Measurement



Smarter, Better, Stronger!

Features



Electric adjustable saddle Excalibur Sport

The position of the saddle of the excalibur sport can be adjusted in height, length and angle to suit all users.

The saddle of the ergometer can be adjusted horizontally in a range of 252 mm and the saddle height in a range of 388 mm using the Control Unit or LEM.

The Test Subject can be seated on the saddle while adjusting.



Electric adjustable handlebar Excalibur Sport

The position of the handlebar of Excalibur Sport is completely adjustable in height and length.

The handlebar of the ergometer can be adjusted horizontally in a range of 169mm and vertically in a range of 390mm using the Control Unit or LEM software. The Test Subject can use the handlebar while adjusting.

**10
watt**

Extreme low start up load 10W

The extreme low start-up load of 10 watts and the adjustability in small steps of 1 watt make this ergometer perfectly suitable for many different applications. The standard control unit shows multiple ergometry parameters and you can determine your specific default setting and start-up menu.



Low noise

Due to accurate manufacturing and the careful choice of materials the product has an extremely low noise level.



Accurate over a long period of time

The Lode ergometers are supplied with an electro-magnetic braking mechanism of Lanooy (eddy current). The biggest advantage of this braking system compared to a friction braking system is the absolute accuracy and the accuracy over time. Moreover, friction braking systems have more wearing parts.



Compatible with ECG and pulmonary devices

The Lode ergometers have digital interfaces and can be controlled easily by all known stress ECG and pulmonary devices available in the world. This is one of the reasons why the Lode ergometers are very popular worldwide.



Exchangeable pedals

The cranks of the ergometer are suitable for almost all available clip systems so cyclists can perform a test with their own favorite pedals.



Designed to be sweat-proof

The housing of the ergometer is designed in such way that sweat does not have the chance to drip into the mechanical parts and cables are protected. This ensures a long lifetime and makes the ergometer insensitive for malfunction.



RS232 connectivity

RS232 ports enable connectivity to most ECG and ergospirometry devices as well as PC's.



LEM compatible

This product can be used with Lode Ergometry Manager (LEM) software to manage data and to apply specific protocols when a Communication card or Network card is present

The new Excalibur Sport with Pedal Force Measurement



Smarter, Better, Stronger!

The new Excalibur Sport with Pedal Force Measurement can also be extended with the following options:

0-Watt start-up system

Lowest possible startup power



Partnumber: 906805

USB to Serial converter

Easy connection



Partnumber: 226012

Adjustable sports cranks incl. pediatric range

Optimal force application



Partnumber: 925808

Easy saddle exchange option

Fast change of saddle to suit all users



Partnumber: 925807

SpO2 for control unit with touch panel (extra long cable)

Oxygen saturation



Partnumber: 945822

LEM 10 - Module Wingate Test plus


Easy to operate Sprint test for explosive



Partnumber: 955915

LEM 10 - Module Åstrand


Reproducible test



Partnumber: 955916

LEM 10 - Module Export


Export your data to MS Excel



Partnumber: 955920

LEM 10 - Module Architect


Creating protocols with customer specific



Partnumber: 955921

Ambient sensor pack

Check environmental conditions during test



Partnumber: 945827

Blood Pressure with ECG trigger for bicycle ergometer with ECG trigger



Partnumber: 945828

Bluetooth Smart heart rate

Heartrate available within an extreme wide



Partnumber: 945833

The new Excalibur Sport with Pedal Force Measurement



Smarter, Better, Stronger!

Specifications

Workload

Minimum load	10 W
Maximum peak load	3000 W
Isokinetic workload control	✓
Minimum load increments	1 W
Hyperbolic workload control	✓
Linear workload control	✓
Fixed torque workload control	✓
Maximum rpm independent constant load	180 rpm
Minimum rpm independent constant load	30 rpm
Electromagnetic "eddy current" braking system	✓

Accuracy

Workload accuracy below 100 W	2 W
Workload accuracy from 100 to 1500 W	2 %
Workload accuracy over 1500 W	5 %

Comfort

Toeclips on pedals		✓
Q-factor	147 mm	
Vertical seat adjustment maximum	938 mm	36.9 inch
Vertical seat adjustment minimum	550 mm	21.7 inch
Horizontal seat adjustment minimum	72 mm	2.8 inch
Horizontal seat adjustment maximum	324 mm	12.8 inch
Allowed user weight	225 kg	496 lbs
Horizontal handlebar adjustment minimum	229 mm	9 inch
Horizontal handlebar adjustment maximum	60 mm	2.4 inch
Vertical handlebar adjustment minimum	465 mm	18.3 inch
Vertical handlebar adjustment maximum	855 mm	33.7 inch

User Interface

English user interface	✓	
Norwegian user interface	✓	
Czech user interface	✓	
Danish user interface	✓	
Dutch user interface	✓	
French user interface	✓	
German user interface	✓	
Italian user interface	✓	
Japanese user interface	✓	
Korean user interface	✓	
Polish user interface	✓	
Portugese user interface	✓	
Russian user interface	✓	
Spanish user interface	✓	
Turkish user interface	✓	
Ukrainian user interface	✓	
Terminal operation mode	✓	
Screen size (diagonal)	17.8 cm	7 inch
Touchscreen	✓	

Connectivity

Lode interface protocol	✓
Ergoline P10 interface protocol	✓
Ergoline P4 interface protocol	✓
Schiller interface protocol	✓
Bosch EKG 506 DS interface protocol	✓
USB connector	✓
RS232 out connector	✓

Dimensions

Product length (cm)	200 cm	78.7 inch
Product width (cm)	100 cm	39.4 inch
Product height	70 cm	27.6 inch
Product weight	100 kg	220.5 lbs

The new Excalibur Sport with Pedal Force Measurement



Smarter, Better, Stronger!

Power requirements

100 / 230V AC 50/60 Hz	✓	
V AC	100 - 240 V	
Phases	1	
Frequency	50/60 Hz	
Power consumption	160 W	
Power cord length	250 cm	98.4 inch
Power cord IEC 60320 C13 with CEE 7/7 plug	✓	

Standards & Safety

IEC 60601-1:2012 - pending	✓
ISO 13485:2016 compliant	✓
ISO 9001:2015 compliant	✓

Included parts

PC included for PFM	✓
Bluetooth dongle	✓

Pedal Force Measurement

Rotational measurement resolution	2 °
Pedal Force accuracy	1 N

Order info

Partnumber: 965920

**Specifications are subject to change without notice.*